

2-CORE XLPE,SWA,HFFR SHEATHED CABLES AS PER QCS 2014

2C X 300 Sq.mm CU/XLPE/SWA/HFFR

International Designation: CU/XLPE/SWA/HFFR

Nexans Ref.: 22300SXZSHS30BS0

2-CORE XLPE,SWA,HFFR SHEATHED CABLES AS PER QCS 2014

DESCRIPTION

Scope

This specification covers two core, XLPE insulated cables for use on the Qatar Power Systems ,Street lightning and Small wiring systems. These cables are complying with BS 6724 and QCS 2014 Standards .

Design

1. Conductor

Plain annealed high-conductivity Stranded Copper Class 2 conforming to BS EN 60228

2. Insulation

XLPE insulation Type GP8 conforming to BS 7655-1

3. Filling or Bedding

Extruded HFFR

4. Armour

Single layer of Galvanised Steel Wires (GSAW)

5. Outer Sheath


Halogen Free Flame Retardant (HFFR)

- Flame retardant : IEC60332-3-24 CAT C

- Colour : Black

Marking

2 X 300 CU/XLPE/SWA/HFFR 600/1000 V BS 6724 MADE IN QATAR QICC-
NEXANS Years Meters



STANDARDS

International
IEC 60332-3-24 Cat.C

National BS 6724



Conductor flexibility
Stranded class 2



Halogen free
Yes



Rated Voltage Uo/U (Um)
0.6/1 kV



Max.conductor temp.in service
90 °C



Bending factor when laying
12 (xD)



Flame retardant
Yes

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 1/19/22 www.nexans.qa Page 1 / 2

QICC

A NEXANS COMPANY

2-CORE XLPE,SWA,HFFR SHEATHED CABLES AS PER QCS 2014

2C X 300 Sq.mm CU/XLPE/SWA/HFFR

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Conductor shape	Circular
Conductor flexibility	Stranded class 2
Armour type	Galvanized steel wires
Colour	Black
Core identification	Red,Black
Halogen free	Yes
Inner sheath	Halogen free flame retardant
Insulation	XLPE
Outer sheath	Halogen free flame retardant

Dimensional characteristics

Number of cores	2
Conductor cross-section	300 mm ²
Approximate weight	8729 kg/km
Nominal armour wire diameter	2.5 mm
Nominal insulation thickness	2.0 mm
Nominal outer diameter	59.5 mm

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	0.6/1 kV
Max. DC resistance of the conductor at 20°C	0.0601 Ohm/km
Permissible current rating in open air	628 A
Permissible current rating when buried	419 A
Thermal soil resistivity dry zone	2.5 °K.m/W
Voltage drop, 3 conductors	0.18 V/A.km

Usage characteristics

Max. conductor temperature in service	90 °C
Short-circuit max. conductor temperature	250 °C
Bending factor when laying	12 (xD)
Ambient air temperature	30 °C
Ambient ground temperature	20 °C
Laying depth, center of system	700 mm
Max. pulling force during laying	50 N/mm ²
Flame retardant	Yes